


Salt and sand spreader

- Park Ranger 2150



Standard equipment:

- Durable material** All parts that get in contact with salt and sand are rust free, made of synthetic material or stainless steel.
- Stirrer** The stirrer prevents blocking, crushes lumps and ensures precise and uniform spreading - and thereby even thawing of the ground. Made of hardened Hardox steel the stirrer fingers are extremely robust.
- Material storage** There is space for extra bags of salt and sand on top of the hopper grate, enabling the operator to fill the salt and sand spreader on site. Please note the maximum loading capacity.
- Stand** A stand for attaching/detaching is delivered with the spreader as standard. The stand has wheels, making it easy to move the spreader into storage without heavy lifting.
- Tarpaulin cover** A cover keeps the material dry and thereby indirectly improve the spreading accuracy.

Extra equipment (options):

- Auger cover for vacuum salt** The cover ensures that tiny material such as vacuum salt, does not just run out of the spreader, which reduces the waste and increase the operation efficiency.
- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	2510
Width	mm	1015
Height with cabin	mm	1935

Storage dimensions

Length with stand	mm	1175
Width	mm	800
Height with stand	mm	1350

Weights

Weight with cabin ¹⁾	kg	860
Payload with cabin	kg	440
Weight (spreader)	kg	97
Weight - stand	kg	31

Spreader

Volume	l	210
Spreader load, max.	kg	350
Loading height	mm	1250

Performance

Spreading width	mm	1000-5000
Operating speed	km/h	1-16

CE certified according to EU directive

¹⁾ Includes: salt and sand spreader, 75 kg operator and 90% fuel capacity.

